



- 1 -

## TITLE OF THE INVENTION

PERIPHERAL EQUIPMENT OF COMPUTER

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

5 The invention relates to peripheral equipment of a computer connected to a computer via a network.

## 2. Description of the Related Art

Combined equipment having many functions, such as a print function, a copy function, a facsimile function  
10 and an electronic mail function is a type of peripheral equipment of a computer. The combined equipment is connected to a network, such as a LAN.

Maintenance of such combined equipment is performed by using, for example, a PC (a personal  
15 computer) connected to the same network. In order that a maintenance operator may perform maintenance on the combined equipment, using a PC with an installed maintenance tool, the maintenance operator has to enable communication between the PC and the combined  
20 equipment. More specifically, the maintenance operator needs to obtain an appropriate IP address assigned by a user of the combined equipment and set up an IP address in the PC for maintenance.

However, the maintenance operator may not obtain  
25 permission for temporary use of the IP address or authorization for access to the network from the standpoint of the security on the side of the user.

- 2 -

In this case, the maintenance operator disconnects the combined equipment from a user's network environment and connects the combined equipment directly to the PC for maintenance, by a cross cable or the like.

5           In this case, the maintenance operator must change the network setup of the PC in accordance with the network setup of the combined equipment in order to enable network communication between the PC for maintenance and the combined equipment.

10           However, it becomes impossible for the maintenance operator to perform maintenance using the network when changes cannot be made in the network setup of the PC. Thus, the need arises to connect the PC for maintenance to the combined equipment by means of a method other  
15           than a LAN, such as a serial connection. To realize this connection, some combined equipment is provided with a local I/F for direct connection and a maintenance function using the local I/F.

20           To change the network setup of the PC for the purpose of maintenance of the combined equipment, the maintenance operator has heretofore had to check the network setup of the combined equipment and perform setup on the PC in accordance with the network setup of the combined equipment before starting maintenance.  
25           Thus, a problem exists: that is, time is required before the maintenance can start.

Moreover, the maintenance operator is required to

- 3 -

have such knowledge and skill that he/she can change the network setup of the PC in accordance with the on-the-spot network environment.

Moreover, the maintenance operator may change the  
5 network setup of the combined equipment for the purpose of the maintenance of the combined equipment, and in this case, he/she needs to take notes of the current network setup without fail before changing the setup of the combined equipment. If the maintenance operator  
10 forgets to restore the network setup of the combined equipment to its original state or makes a mistake in restoration in taking notes of the current network setup, it then becomes impossible to connect the combined equipment to the network, and this causes  
15 the user a great deal of trouble.

Moreover, when the combined equipment includes a device for local connection, such as a serial I/F, and a function using the device so as to prepare for no permission for access to the network, this leads to  
20 a rise in costs of hardware and software.

It is an object of the invention to provide peripheral equipment of a computer, which can change the network setup of equipment in a short time by a simple operation, and thus allows a maintenance  
25 operator to perform maintenance of the equipment with ease.

- 4 -

## BRIEF SUMMARY OF THE INVENTION

According to an aspect of the present invention, there is provided peripheral equipment of a computer which comprises: a communication section connected to the computer via a network; an operation section to perform an operation of changing a network setup of the communication section; a first storage section to save a current network setup value set in the communication section; a second storage section to previously store a fixed network setup value; means for saving in the first storage section the network setup value set in the communication section in accordance with an operation command from the operation section; and means for setting in the communication section the fixed network setup value stored in the second storage section, in place of the saved network setup value.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

## BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and comprise a part of the specification, illustrate presently embodiment of the invention, and together

- 5 -

with the general description given above and the detailed description of the embodiment given below, serve to explain the principles of the invention.

FIG. 1 is a block diagram of a network system  
5 showing an embodiment of the invention;

FIG. 2 is a block diagram showing a configuration of combined equipment of the embodiment;

FIG. 3 is a block diagram showing a configuration of the network system, which is used to perform  
10 maintenance of the combined equipment of the embodiment by using a PC for maintenance;

FIG. 4 is an illustration showing a display screen provided on an operation panel of the combined equipment of the embodiment, which is used to perform  
15 the maintenance;

FIG. 5 is a flowchart showing a process of changing a network setup value by a main control section of the combined equipment of the embodiment, which is used to perform the maintenance; and

20 FIG. 6 is a flowchart showing a process of restoring the network setup value by the main control section of the combined equipment of the embodiment.

#### DETAILED DESCRIPTION OF THE INVENTION

25 An embodiment of the invention will be described below with reference to the drawings.

As shown in FIG. 1, a LAN is used as a network environment. A HUB 1 is connected to a plurality of

- 6 -

client PCs 3 through a LAN cable 2, and the HUB 1 is also connected to combined equipment 4 which is peripheral equipment of a computer, through the LAN cable 2.

5           As shown in FIG. 2, the combined equipment 4 comprises a main control section 41 which controls many functions of the equipment, an operation panel 42 having a touch panel with various types of keys on a display screen, and a scanner section 43 which  
10 captures image information from an original document.

          The combined equipment 4 also comprises an image processor 44 which processes image information captured by the scanner 43, a printer section 45 which prints image information, character information and the like,  
15 and an information storage section 46 which stores image information, character information and the like.

          The combined equipment 4 also comprises a network controller 47 which is connected to the LAN cable 2 and functions as a communication section which communicates  
20 with the client PC 3 and the like via the network.

          The combined equipment 4 also comprises a first storage section 48 to save the current network setup value set in the network controller 47, and a second storage section 49 to previously store a fixed network  
25 setup value.

          The parts constituting the combined equipment 4 are electrically connected to one another through a bus

- 7 -

line 50. The main control section 41 comprises a CPU and a ROM, and the main control section 41 is configured to control the parts in accordance with program data stored in the ROM.

5           The information storage section 46 is comprised of a dynamic RAM.

          As the first storage section 48, used is a device which is rewritable during operation of the combined equipment 4 and whose contents are not erased even when  
10       the combined equipment 4 is turned off under operation, such as a nonvolatile RAM, a flush ROM or an HDD.

          As the second storage section 49, used is a device whose contents are not erased even when the combined equipment 4 is turned off, such as a nonvolatile RAM,  
15       a flush ROM or an HDD. At the time of manufacture, necessary values are previously stored in the second storage section 49.

          In the network environment shown in FIG. 1, TCP/IP is used as a protocol, and IP addresses are assigned as  
20       the network setup values to the client PCs 3 and the combined equipment 4.

          A value other than the IP address may be used as the network setup value.

          For example, the IP address 123.123.123.123 is  
25       assigned to the combined equipment 4.

          FIG. 3 shows the network environment shown in FIG. 1 in which a maintenance operator performs

- 8 -

maintenance of the combined equipment 4 using a PC 5 for maintenance with an installed maintenance tool.

More specifically, the LAN cable 2 connected to the HUB 1 is disconnected from the combined equipment 4. Then, a cross cable 6 is used to connect the PC 5 for maintenance to the combined equipment 4. Also when the cross cable 6 is used, TCP/IP is used as the protocol. In this case, the IP address of the combined equipment 4 is set to, for example, 192.168.1.1, and the IP address of the PC 5 for maintenance is set to, for example, 192.168.1.2.

At the time of manufacture, the IP address 192.168.1.1 of the combined equipment 4 is previously stored in the second storage section 49 as the fixed network setup value. Also the IP address 192.168.1.2 of the PC 5 for maintenance is previously set in a memory in the PC.

The IP address 192.168.1.1 is an address which enables communication with the PC 5 for maintenance in which the IP address 192.168.1.2 is set.

As described above, the IP address 192.168.1.2 of the PC 5 for maintenance is previously set, and thus, connection can take place quickly on the spot.

Then, the maintenance operator connects the combined equipment 4 having the set IP address 192.168.1.1 to the PC 5 for maintenance having the set IP address 192.168.1.2. This connection allows



- 9 -

communication between a maintenance function of the combined equipment 4 using the network and the maintenance tool installed in the PC 5, so that the maintenance operator can perform maintenance.

5           Next, a description is given with regard to switching of the network setup value of the combined equipment 4.

          The first storage section 48 is used to save the IP address 123.123.123.123 indicative of the current network setup value.

          FIG. 4 shows a display screen with the touch panel provided on the operation panel 42 of the combined equipment 4. The screen is a screen which only a specific person such as the maintenance operator  
15           can use with the touch of the touch panel, and the maintenance operator causes the screen to appear after connecting the PC 5 to the combined equipment 4 by use of the cross cable 6. Then, the maintenance operator touches a maintenance mode key 421 on the screen.

20           When the maintenance mode key 421 is touched, the main control section 41 performs a changing process shown in a flowchart of FIG. 5.

          First, in step ST1, the IP address 123.123.123.123 indicative of the current network setup value set in  
25           the network controller 47 is saved in the first storage section 48.

          Then, in step ST2, the IP address 192.168.1.1

- 10 -

indicative of the network setup value is fetched from the second storage section 49.

Finally, in step ST3, the fetched IP address 192.168.1.1 is set in the network controller 47 so as  
5 to reset a network function.

Thus, the IP address set in the network controller 47 is changed from 123.123.123.123 to 192.168.1.1.

In the changing process, a first touch of the maintenance mode key 421 allows the combined equipment  
10 4 to switch to the setup for maintenance, and the display is inverted.

Then, in this inverted state, another touch of the maintenance mode key 421 allows the main control section 41 to perform a restoring process shown in  
15 a flowchart of FIG. 6.

First, in step ST11, the IP address 123.123.123.123 indicative of the network setup value saved in the first storage section 48 is fetched from the first storage section 48.

20 Then, in step ST12, the fetched IP address 123.123.123.123 is set in the network controller 47 so as to reset the network function.

Thus, the IP address of the network controller 47 indicating the network setup value returns from  
25 192.168.1.1 to 123.123.123.123.

Accordingly, to perform the maintenance of the combined equipment 4, the maintenance operator

- 11 -

disconnects the LAN cable 2 connected to the HUB 1 from the combined equipment 4, and then connects the PC 5 for maintenance to the combined equipment 4 by using the cross cable 6.

5           Then, the maintenance operator operates the operation panel 42 of the combined equipment 4 so as to cause the screen shown in FIG. 4 to appear, and then touches the maintenance mode key 421.

          Thus, under the control of the main control  
10       section 41, the IP address 123.123.123.123 set in the network controller 47 is saved in the first storage section 48, and then the IP address 192.168.1.1 stored in the second storage section 49, in place of the saved IP address, is set in the network controller 47.

15           This permits communication between the maintenance function of the combined equipment 4 using the network and the maintenance tool installed in the PC 5, and thus the maintenance operator performs maintenance of the combined equipment 4 by using the maintenance tool  
20       of the PC 5.

          When the maintenance is over, the maintenance operator again touches the maintenance mode key 421. Thus, the IP address 123.123.123.123 saved in the first storage section 48 is again set in the network  
25       controller 47, so that the network function is reset.

          In this state, the maintenance operator restores the display screen of the operation panel 42 to the

- 12 -

original display screen, then disconnects the cross cable 6 from the combined equipment 4, and then connects the LAN cable 2 connected to the HUB 1 to the combined equipment 4. This makes it possible for the  
5 combined equipment 4 to again communicate with the client PCs 3 via the network.

In a series of such operations, even if the maintenance operator forgets to restore the IP address of the network controller 47 to the original IP address  
10 thereof after the end of maintenance, the maintenance operator easily becomes aware that he/she has forgotten to perform the operation of restoring the IP address to the original IP address, because the maintenance mode key 421 remains reversed. Moreover, even a user, as  
15 well as the maintenance operator, can easily perform the operation of restoring the IP address to the original IP address.

As described above, the maintenance operator can simply switch the combined equipment 4 to the network  
20 setup for maintenance without discarding the current network setup of the combined equipment 4.

Therefore, the maintenance operator can quickly perform maintenance using the network function under no influence of uncertainties and variables, that is, the  
25 network environment which is used by the user who owns the combined equipment 4.

When the maintenance is over, the maintenance

- 13 -

operator can surely restore the network setup to its original state by a simple operation.

Moreover, the combined equipment 4 and the PC 5 for maintenance can be surely connected by the LAN, and therefore the combined equipment 4 does not require a local I/F for maintenance as standard equipment, so that this allows a reduction in costs of hardware and software.

Although the invention is described above by referring to the above-mentioned embodiment using the combined equipment having many functions as the peripheral equipment of a computer, the invention is not necessarily limited to this embodiment. More specifically, the invention may be applied to any peripheral equipment as long as the peripheral equipment communicates with a computer via a network.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.